


FENDER 999A-L0125A-04

Luminaire for pole tilt FENDER IP66 LED SMD 21W 3025lm(2500lm) CRI70 3000K 110°
114mm Anthracite



The Luminaire for Post Fender, with a compact design in anthracite finish, self-cleaning and optimized for heat dissipation, allows assembling both vertical pole and horizontal arm, can be tilted +/- 15°. Includes IP connector to facilitate assembly. Available with a symmetric optics and another asymmetric, it is offered with two power levels, both at 3000K and 4000K. With IP66 and IK08 protection degrees and a high resistance to corrosion, make it ideal for exterior lighting applications of roads, roads or large spaces.

GENERAL DATA

Category	Bollards and columns
Family	Fender
Finish	[04] Anthracite
Location	Outdoor
Body material	Aluminum
Diffuser material	Transparent glass
ETIM class	EC000062
EAN	8433264120955

LIGHT SOURCES AND BEAMS

Sources	LED SMD 21W 3025lm(2500lm) 3000K CRI70
Energy efficiency	E (3000K)
Beam	110° - Direct asymmetric


TECHNICAL DATA

Dimensions	Length x Height x Width x Pole's top diameter (mm): 479 x 114 x 211 x 60
IP	IP66
IK	08
Protection class	Class I
Frequency	50/60 Hz
Input voltage	110-240V AC V
Power factor	0.95
Auxiliary gear	Electronic
Auxiliary equipment brand	Meanwell
Operating temperature range	-20 - 50 °C
Lifetime	78,000 h
LED lifetime L	80
LED lifetime B	10
Weight	2.7 Kg
Cable outlets	1
Tilt angle	30.0 °
ECORAE category I	-
ECORAE I	0.7

PHOTOMETRIC DATA

FENDER 999A-L0125A-04

Luminaire for pole tilt FENDER IP66 LED SMD 21W 3025lm(2500lm) CRI70 3000K 110°
114mm Anthracite



NOTES

IP connector included


Corrosion resistance (salt spray: > 1000h)

Optic type III

FENDER 999A-L0125A-04

Luminaire for pole tilt FENDER IP66 LED SMD 21W 3025lm(2500lm) CRI70 3000K 110°
114mm Anthracite

RECOMMENDED ACCESSORIES



C03B-32-39

TopØ60 pole POSTES 3000mm
Anodized aluminum



C06B-31-02

TopØ60 pole POSTES 2400mm
Black



C30E-31-38

TopØ60 pole POSTES without
registration 2500mm Zinc plated
steel



C30E-32-38

TopØ60 pole POSTES with
registration 2500mm Zinc plated
steel




C30F-31-38

TopØ60 pole POSTES without
registration 3000mm Zinc plated
steel



C30F-32-38

TopØ60 pole POSTES with
registration 3000mm Zinc plated
steel



C04A-32-02

TopØ60 pole POSTES Resina Mod.
3000mm Black

FENDER 999A-L0125A-04

Luminaire for pole tilt FENDER IP66 LED SMD 21W 3025lm(2500lm) CRI70 3000K 110°
114mm Anthracite

COMPLEMENTARY IMAGES

